



Feature:

- ◆ Supersonic frequency harden and precision ground bedway available on request
- ◆ Safety magnetic switch of lock key switch available on request



主要技术参数

MAJOR SPECIFICATIONS

床身上最大回转直径 Max. swing over bed	280mm
中拖板上最大回转直径 Max. Swing over cross slide	140mm
两顶尖间最大距离 Distance between centers	610mm
主轴通孔直径 Spindle bore	26mm
主轴孔莫氏锥度 Taper of spindle bore	M.T. #4
主轴转速 Range of spindle speed	125-2000 rpm.
纵向切削量范围 Range of longitudinal feeds	0.1-0.25mm/rev.
公制螺距范围 Range of metric threads	0.3-2.5mm
英制螺距范围 Range of inch threads	8-35TPI.
刀杆最大截面尺寸 Max. Size of tool shank	14X14mm
尾座套筒莫氏锥度 Taper of tailstock bore	M.T. #3
电机功率 Power of motor	750 W.

包装尺寸及重量——整包/Unitary packaging size and weight

Type of lathes	Packing dimensions	Net weight	Gross weight
CQ6128X610	1480X750X1460 mm	268 kg	367 kg

包装尺寸及重量——分包/Asunder packaging size and weight

Type of lathes	Packing dimensions	Net weight	Gross weight
CQ6128X610	1320X650X610 mm	218 kg	258 kg

标准随机附件/STANDARD ACCESSORIES

三爪卡盘/3-Jaw chuck (ϕ 125mm)
 交换齿轮/Change gears set
 莫氏3号及莫氏4号呆顶尖/M.T. #3 & #4 dead centers
 工具箱及工具/Tool box with tools

特殊选购附件/OPTIONAL ACCESSORIES

四爪卡盘/4-Jaw chuck (ϕ 125mm)
 花盘/Face plate
 中心架/Steady rest
 跟刀架/Follow rest
 活动顶尖/M.T. #3 live center
 挡屑板/Splash guard
 油盘/Oil tray
 床脚/Foot stands
 油枪/Oil gun
 工作灯/Work light
 钻夹头+钻夹杆/Drill chuck with arbor
 丝杠护罩/Leadscrew guard