



Features

- Independent hydraulic power pack
- Moveable foot pedal with independent up & down pedals
- Bending attachment as standard—includes top bending blade with frame and bottom multi vee die.
- Ideal for bending up brackets
- Moveable bottom table
- Bending attachment can be removed and therefore used as a standard press
- Large solid tables
- Heavy duty construction

| Specifications | YLM-50Z | YLM-100Z | YLM-150Z |
|----------------------------|-------------------------|-------------------------|-------------------------|
| Capacity | 50 Ton | 100 Ton | 150 Ton |
| Max. Pressure | 280 Bar | 320 Bar | 500 Bar |
| Pump Capacity | 7.5 L/Min | 32 L/Min | 32 L/Min |
| Speed of Shaft | 300 mm/Min | 1020 mm/Min | 1020 mm/Min |
| Rapid Down Speed | 9 mm/Sec | 17 mm/Sec | 17 mm/Sec |
| Slow Speed Down | 9 mm/Sec | 6 mm/Sec | 6 mm/Sec |
| Up Speed | 9 mm/Sec | 23 mm/Sec | 23 mm/Sec |
| Width of Work Table | 800 mm | 1300 mm | 1300 mm |
| Oil Cylinder Stroke | 250 mm | 300 mm | 270 mm |
| Worktable Up & Down Stroke | 675 mm | 540 mm | - |
| Weight | 780 Kg | 2100 Kg | 2300 Kg |
| Dimensions | 1430 x 750 x 1970 mm | 2100 x 750 x 2250 mm | 2050 x 750 x 2350 mm |